



ISSN : 0973-7057

Int. Database Index: 663 www.mjil.clarivate.com

## Bioaccumulation of heavy metal by water hyacinth

Rupak Kumari\*

Department of Botany, RJM College, Saharsa, B.N.M.University, Madhepura, Bihar, India

Received : 18<sup>th</sup> May 2020 ; Revised : 22<sup>th</sup> June 2020

**Abstract :** Aquatic plants are well known accumulator of heavy metals from wetland. The objective of this study is to evaluate the capacity of *Eichhornia crassipes* to accumulate lead from municipal waste water. Young plant of *Eichhornia crassipes* of equal size were grown in municipal waste water for 20 days. The plant in the experiment removed 50% lead. Removal of metal from waste water was fast in the first 10 days. Bio-concentration factor (BCF) was more than 1000. *Eichhornia* was found to be suitable plant for removal of heavy metal from waste water.

**Key words:** BCF, *Eichhornia crassipes*, bioaccumulation

### INTRODUCTION

Heavy metals are metallic chemical elements with a high atomic weight and density much greater than water. They are highly toxic and cause adverse effects even at very low concentrations e.g. mercury (Hg), cadmium (Cd), arsenic (As), chromium (Cr), thallium (Tl), and lead (Pb). They are added to the aquatic system, either naturally by slow leaching from soil/rock to water or through anthropogenic sources.<sup>1-5</sup> These heavy metals are not biodegradable; hence there is a need to develop such remediation technique, which should be efficient, economical and rapidly deployable in a wide range of physical settings.<sup>6</sup>

Wetland treatment technology offers a comparative advantage over conventional, mechanized treatment systems as the level of self-sufficiency, ecological balance,

and economic viability is greater. Phytoremediation technology consists of mitigating pollutant concentrations in contaminated water bodies with naturally occurring or genetically engineered plants that have ability to accumulate, degrade or eliminate metals, pesticides, solvents, explosives, crude oil, and its derivatives *etc.*<sup>7,8</sup>

### MATERIAL & METHODS

To assess the heavy metal absorption capacity of *Eichhornia*, test was conducted in three cylindrical tanks of 1000 L capacity with 80cm radius and 50cm depth. In each tank 20cm deep 400 L municipal waste water was added. Each tank was seeded with 4kg fresh and young *Eichhornia* plants which were taken from an unpolluted pond. 1 tank was taken as control. Plants were thoroughly washed with clean water before seeding. In waste water Lead was analysed in initial, 5<sup>th</sup>, 10<sup>th</sup>, 15<sup>th</sup> and 20<sup>th</sup> day. Metal concentration of each plant was analysed on initial and final stage of experiment.

\*Corresponding author :

Phone : 8207620024

E-mail : rupak852201@gmail.com

CHEMICAL ANALYSIS

50ml of water sample at each level (in initial, 5<sup>th</sup>, 10<sup>th</sup>, 15<sup>th</sup> and 20<sup>th</sup> day) were digested in 2M HNO<sub>3</sub> at 95°C for 2 hours and made upto 100ml in a volumetric flask with distilled water. Digested samples analysed for metal using atomic absorption spectrophotometer.

The plant samples were separated into root and leaves to determine the accumulation trend from waterto the roots and to the leaves. They were each dried in an oven at 60°C till well dried. The dried samples were ground before digestion. 500 mg of dried weight of each fraction were digested with 10 mL of HClO<sub>4</sub> and HNO<sub>3</sub> mixture (1:3) at about 80°C for 4 hours. The resulting cleared coloured solutions were made up to the mark in a 25 ml volumetric flask with the distilled water. All the reagents that were used were of analytical grade and all the reaction vessels were treated well to avoid external contributions of the metals. Sample blanks were analysed to correct the possible external contributions while replicate samples were also evaluated and all the analyses were done in triplicate to ensure reproducibility of the results. The digested samples were analysed for lead by atomic absorption spectrophotometer.

In the present investigation, the bioconcentration factor (BCF) of heavy metal (Lead) within *Eichhornia crassipes* was calculated by following formula:

$$BCF = \frac{\text{Trace element conc. in harvested plant } \left(\frac{mg}{kg}\right)}{\text{Initial conc. of element in water } \left(\frac{mg}{l}\right)}$$

RESULT

The final concentration of lead in waste water treated with *Eichhorniacressipes* was lower than concentration of lead in control tank. The bio-concentration factor (BCF) in the present study is given in Table.

Table. 1

Metal	BCF in Root	BCF in Leaves	BCF in Plant
Pb	7625.54	2116.67	4866.15

REFERENCES

1. APHA. 2002. Standard Methods for the Examination of Water and Wastewater, American Public Health Association, AWWA, and WPCF, Washington DC.
2. Arora A., Saxena S., Sharma D. K. 2006. Tolerance and phytoaccumulation of chromium by three *Azolla* species. *World Journal of Microbiology & Biotechnology*. **22**: 97–100.
3. Brook R. R., and Robinson B. H. 1998. Aquatic phytoremediation by accumulator plants. In Plants that hyperaccumulate heavy metals: Their role in phytoremediation, microbiology, archaeology, mineral exploration and phytomining, ed. Brook, R.R, 203–226. Wallingford, UK: *CABI International*.
4. Cheng S. 2003. Heavy metals in plants and phytoremediation. *Environmental Science and Pollution Research*. **10**: 335–340.
5. Dhir B, Sharmila P, Saradhi P. P. 2009. Potential of aquatic macrophytes for removing contaminants from the environment. *Critical Reviews in Environmental Science and Technology*. **39**: 754–781.
6. Dhote S., Dixit S. 2009. Water quality improvement through macrophytes- a review. *Environmental Monitoring and Assessment*. **152**:149–153.
7. Lissy P. N. A., Madhu B. G. 2010. Removal of heavy metals from waste water using water hyacinth. *Proc. of Int. Conf. on Advances in Civil Engineering*. 42-47.
8. Mahmood Q., Zheng P., Islam E., Hayat Y., Hassan M. J., Jilani G. 2005. Lab Scale Studies on Water Hyacinth (*Eichhornia crassipes* Marts Solms) for Bio treatment of Textile Wastewater *Caspian. Journal of Environmental Sciences*. **3(2)**: 83-88.

\*\*\*

